

# SPECIFICATIONS

FR1057107

Page 1 of 2

ITEM NO.	DESCRIPTION	CHECK IF AS SPECIFIED	DESCRIBE FULLY IF NOT AS SPECIFIED
1.	<b>Softener System:</b> *Complete Packaged Automatic System *All material FDA Approved *Including, but not limited to: Softener, Controls and related Piping. Initial Charge and System placed in Operation.		
	<b>Remove and dispose existing Water Softener tank.            Furnish and install new Water Softener tank.</b>		
	<u><b>INSTALLATION:</b></u> <ul style="list-style-type: none"> <li>Complete installation and test water softener to meet manufacturer installation instructions and recommendations. Installation will be performed by an authorized/ trained technician.</li> </ul>		
	<u><b>MANDATORY SECURITY BACKGROUND CLEARANCE:</b></u> All bidders must successfully pass a security background clearance in order to obtain access to the institution for the scheduled pre-bid visit. All bidders must submit personal information to provide adequate time for completion of a security background clearance. <b>This security background clearance must be done for every individual who will be attending the site visited.</b> The following information must be faxed to 509-544-3505, Attn: <b>Todd Kusler, Phone # 509-543-5814</b>		

# SPECIFICATIONS

FR1057107

Page 2 of 2

	<p>Full name of the individual (including the middle name)</p> <p>Date of Birth</p> <p>Social Security Number</p> <p>Current home address</p>		
	<p><b><u>SECURITY BRIEFING AND TOOL INVENTORY</u></b></p> <p>All vendors on site will have to have a quick briefing on security issues and interaction with offenders. They must submit to an inventory of all tools that will be on the job site.</p>		
	<p><b>Brine System:</b></p> <p>Polyethylene or Fiberglass</p> <p>Automatic Brine Maker</p> <p>Timer Brining with Safety Float</p>		
	<p><b>Automatic Controls:</b></p> <p>Bronze, Multi-Port, Diaphragm, or Piston-Operated Valve.</p> <p>Automatic Reset Meter used on Multiple Unit Installation,</p> <p>Or 12 day 24 volt Timer on Single Unit.</p> <p>Interlock on Multiple Tank Systems to allow only one unit to</p> <p>Regenerate at a time.</p> <p>3 Years Replacement Warranty on Valve and Timers</p>		
	<p><b>Minerals:</b></p> <p>High Capacity Resin with Minimum Exchange Rate of</p> <p>27,500 Grains per cubic foot when Regenerated</p>		

## SPECIFICATIONS

FR1057107

Page 3 of 2

[illegible]